



PRINT AND CUT MATERIAL INSTRUCTIONS

ColorPrint™ PU (Matte/Gloss) For Use On: 100% cotton | Poly/cotton blends | 100% polyester | Leather | Lycra®/Spandex



Print and Cut Instructions:

- Set heater/dryer to 113°F/45°C
- If heavy saturation ink, dry 1 hour before cutting
- Print, cut, and weed material
- Mask with TTD Easy mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 295°F / 146°C
- Use medium pressure for 15-20 seconds
- Peel carrier hot

Laundering:

- Wait 24 hours before first wash
- Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Compatible with Eco-Solvent, Solvent, and Latex Inks - Not compatible with Inkjet or Laser printers

ColorPrint™ Easy For Use On: 100% cotton | Poly/cotton blends | 100% polyester | Leather



Print and Cut Instructions:

- Print, cut, and weed material
- No dry time required!
- Mask with TTD Easy mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 300°F / 149°C
- Use medium pressure for 15 seconds
- Peel carrier warm

Laundering:

- Wait 24 hours before first wash
- Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Compatible with Eco-Solvent and Solvent Inks - Not for use with Inkjet or Laser printers

ColorPrint™ Extra For Use On: 100% cotton | Poly/cotton blends | 100% polyester | 100% nylon | Leather

Print and Cut Instructions:

- Print, cut, and weed material
- No dry time required!
- Mask with TTD Easy mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 320°F / 160°C
- Use medium pressure for 10-15 seconds
- Peel carrier hot

Laundering:

- Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Compatible with Eco-Solvent, Solvent, and Latex Inks - Not compatible with Inkjet or Laser printers

ColorPrint™ Soft Opaque For Use On: 100% cotton | Poly/cotton blends | 100% polyester | Leather



Print and Cut Instructions:

- Set heater/dryer to 113°F/45°C - 122°F/50°C
- Set cutter force to 30-50 grams to ensure the design will remove from mask
- Allow 30 minutes to 1 hour dry time for detailed designs
- Print, cut, and weed material
- Mask with TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 311°F / 155°C
- Use medium/firm pressure for 15 seconds
- Peel carrier Hot.

Laundering:

- Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Compatible with Eco-Solvent and Solvent Inks - Not compatible with Inkjet or Laser printers

ColorPrint™ Sublithin For Use On: 100% cotton | Poly/cotton blends | 100% polyester | Sublimated polyester



Print and Cut Instructions:

- Set heater/dryer to 113°F/45°C - 122°F/50°C
- Print, cut, and weed material
- Mask with TTD Easy Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 265°F / 130°C
- Use medium pressure for 15 seconds
- Peel carrier warm

Laundering:

- Wait 24 hours before first wash
- Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Hang item to dry

Compatible with Eco-Solvent and Solvent Inks - Not compatible with Inkjet or Laser printers

Hi-5 Print Matte For Use On: 100% cotton | Poly/cotton blends | 100% polyester



Print and Cut Instructions:

- Print, cut, and weed material
- Mask with TTD Easy Mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 250°F / 120°C
- Use medium pressure for 5 seconds
- Peel carrier hot

Laundering:

- Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Compatible with Eco-Solvent, Solvent, and Latex Inks - Not compatible with Inkjet or Laser printers



SiserNA.com